



560 XP®

Husqvarna 560 XP® is developed for professional loggers and skilled land owners. The saw has a ground breaking design and is loaded with innovative solutions for efficient, convenient operation. Our unique X-Torq® engine technology provide more power where you need it, up to 20% less fuel consumption and 75% less exhaust emission. RevBoost™ provide instant high chain speed for extra efficient de-limbing.



X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.




AUTOTUNE

AutoTune gives optimal engine performance throughout automatic engine setting. No time spent on carburettor adjustments. It compensates for different fuels, altitude, humidity, temperature and clogged air filter.



REVBOOST™

Rapid acceleration and higher chain speed for best limbing performance.



AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.

Features

- LowVib® sparing the user's arms and hands
- Adjustable chain oil pump
- Quick-release air filter
- Intuitive, combined choke/stop control
- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Easy to maintain with snap locked cylinder cover
- Maximum durability for tough applications
- Smart Start® for easy starting
- Easy and convenient to handle in any situation.
- Felling marks for correct felling direction
- Fuel level window
- Fuel pump for easy starting
- The retaining function prevents losing the bar nuts.
- Increased safety, inertia activated chain brake

Technical data

Cylinder displacement	59.8 cm ³ / 3.65 cu.inch
Power output	3.5 kW
Maximum power speed	9600 rpm
Fuel tank volume	0.65 lit / 22 fl oz
Fuel consumption	494 g/kWh
Idling speed	2800 rpm
Spark plug	NGK CMR6H
Electrode gap	0.5 mm / 0"
Torque, max.	3.65 Nm/8100 rpm
Oil tank volume	0.33 lit / 0.7 US pint
Oil pump type	Adjustable flow
Oil pump capacity	6-15 ml/min
Equivalent vibration level (ahv, eq) front / rear handle	2.7/3.2 m/s ²
Sound pressure level at operators ear	106 dB(A)
Sound power level, guaranteed (LWA)	118 dB(A)
Chain pitch	.325"
Recommended bar length, min-max	33-60 cm / 13"-24"
Chain speed at max power	21.3 m/s / 69.9 fts
Weight (excl. cutting equipment)	5.6 kg / 12.35 lbs

ARTICLES

966 00 91-13	13" - .325" - H25 - CE,EPA - Europe,US,CA,others	€ 813,-	€ 999.99
966 00 91-15	15" - .325" - H25 - CE,EPA - Europe,US,CA,others	€ 837.39	€ 1,029.99
966 00 91-18	18" - .325" - H25 - CE,EPA - Europe,US,CA,others	€ 845.52	€ 1,039.99

