





T540 XP®

Husqvarna T540 XP® is designed for the high-end top handle saw segment, targeting professional customers like full pro arborists, landscapers, garden contractors and utility services who need excellent performance in combination with the best ergonomics.



AUTOTUNE

AutoTune gives optimal engine performance throughout automatic engine setting. No time spent on carburettor adjustments. It compensates for different fuels, altitude, humidity, temperature and clogged air filter.



X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



INDIVIDUAL GRIP SIZE

The top handle grip size can be set in three alternative sizes, to perfectly fit your hand.



BELT EYE LET

Makes it quick and easy to connect the saw to the climbing harness.

Features

- The light and strong TechLite™ bar makes the saw easier to manouvre.
- Auto return stop switch for easy starting
- Less filter cleanings with Air Injection
- The flip-up tank cap is easy to open.
- LowVib® sparing the user's arms and hands
- Quick-release air filter
- Adjustable chain oil pump
- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Good visibility hand guard
- Fuel level window
- Fuel pump for easy starting
- Increased safety, inertia activated chain brake

Technical data

Cylinder displacement	37.7 cm ³ / 2.3 cu.inch
Power output	1.8 kW
Maximum power speed	10200 rpm
Maximum recommended engine speed	14200 rpm
Idling speed	3000 rpm
Spark plug	NGK CMR6H
Electrode gap	0.5 mm / 0.02 "
Air filter type	Nylon 80μ
Oil tank volume	0.2 lit / 0.42 US pint
Oil pump type	Adjustable flow
Oil pump capacity	3-9 ml/min
Equivalent vibration level (ahv, eq) front / rear handle	3.1/3.2 m/s ²
Sound pressure level at operators ear	104 dB(A)
Sound power level, guaranteed (LWA)	116 dB(A)
Chain pitch	3/8"
Recommended bar length, min-max	30-40 cm / 12"-16"
Chain speed at max power	19.4 m/s / 63.65 fts
Chain gauge	0.05 "
Weight (excl. cutting equipment)	3.7 kg / 8.16 lbs

ARTICLES

965 98 27-12	12" EU, AU, NZ		€ 849.99
965 98 27-14	14" EU, AU, NZ	€ 707.31	€ 869.99

