



## 535RXT

Husqvarna 535RXT is a new brushcutter in the versatile 35 cc class, built for tough commercial use. Top class performance is provided through raw power, unique ergonomics and excellent durability. The machine is equipped with a comfort package including LowVib® and comfort grip handles.



### X-TORQ® ENGINE

The X-Torq® engine design increases torque over a wider rpm range providing maximum cutting power.



### LOWVIB®

Effective anti-vibration dampeners absorb vibration, sparing the user's arms and hands.



### OFFSET HANDLE BAR

Angled handlebar and comfort handles provides excellent grip and working position.



### TRIO-BALANCE

Ergonomic harness with broad back support, shoulder straps and hip belt that distributes the load over a larger area.

## Features

- High handle bar, more leg space
- Auto return stop switch for easy starting
- Grass bevel gear for best cutting performance
- Adjustable handle bar for best comfort
- Fuel pump for easy starting
- Versatile use with combi guard
- Adjustable harness hook eyelet
- Comfortable handle design
- Soft grip handles
- Tap 'n Go trimmer head

## Technical data

Cylinder displacement	34.6 cm <sup>3</sup> / 2.11 cu.inch
Power output	1.6 kW
Maximum power speed	8400 rpm
Maximum recommended engine speed	11500 rpm
Carburettor	Zama C1Q
Fuel tank volume	0.6 lit / 20.29 fl oz
Fuel consumption	480 g/kWh
Idling speed	2900 rpm
Spark plug	Champion RCJ6Y
Electrode gap	0.5 mm / 0.02 "
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Exhaust emissions (HC average)	32 g/kWh
Exhaust emissions (CO average)	196 g/kWh
Exhaust emissions (NOx average)	2 g/kWh
Equivalent vibration level (ahv, eq) front / rear handle	2.5/2.7 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) left / right handle	2.5/2.7 m/s <sup>2</sup>
Sound pressure level at operators ear	96 dB(A)
Sound power level, guaranteed (LWA)	113 dB(A)
Gear ratio	1:1.4
Drive gear angle	35 °
OEM Trimmer head	T35XM12
OEM Grass blade	Multi 300-3
OEM Harness	Balance X
Weight (excl. cutting equipment)	6.2 kg / 13.7 lbs
Tube length	1483 mm / 58.39 inch
Tube diameter	28 mm / 1.1 "

### ARTICLES

966 62 89-01	T35X + Multi 300-3 (1"), All ex US50	€ 699.99
--------------	--------------------------------------	----------

