



543RS



X-TORQ® ENGINE

The X-Torq® engine design increases torque over a wider rpm range providing maximum cutting power.



STANDARD DOUBLE HARNESS

Standard harness for lighter brushcutters.



FUEL PUMP

Fuel pump designed for easy starting.



COMBI-GUARD

The cutting attachment combi-guard can be used with either a grass blade or a trimmer head.

Features

- Robust handle system
- Heavy duty clutch
- Easy to service and maintain starter
- Efficient air filter
- Grass bevel gear for best cutting performance
- Tap 'n Go trimmer head
- Comfortable handle design

Technical data

Cylinder displacement	40.1 cm ³ / 2.45 cu.inch
Power output	1.5 kW
Maximum power speed	9000 rpm
Maximum recommended engine speed	12000 rpm
Carburettor	Walbro
Fuel tank volume	0.75 lit / 25.36 fl oz
Fuel consumption	449 g/kWh
Idling speed	3000 rpm
Spark plug	NGK CMR7H
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Equivalent vibration level (ahv, eq) front / rear handle	3.5/3 m/s ²
Equivalent vibration level (ahv, eq) left / right handle	3.5/3 m/s ²
Sound pressure level at operators ear	95 dB(A)
Sound power level, guaranteed (LWA)	118 dB(A)
Gear ratio	1:1.4
Drive gear angle	30°
OEM Trimmer head	T35 M12
OEM Grass blade	Multi 275-4
OEM Harness	Standard double harness
Weight (excl. cutting equipment)	7.4 kg / 16.31 lbs
Tube length	1483 mm / 58.4 inch
Tube diameter	28.05 mm / 1.1 "

ARTICLES

966 77 99-02	T35 M12 + Multi 275-4 1", DE, FR, NL, SE, DK, FI, NO, UK,GR, ES, PT,HU, RU	€ 455.28	€ 559.99
--------------	--	----------	----------

