



Husqvarna K 760

The Husqvarna K 760 has long been a highly popular all-round power cutter among construction workers and landscapers. By improving a number of large and small details, we've made the machine even more powerful, efficient, reliable and comfortable.



Features Husqvarna K 760

- SmartCarb, a built-in automatic filter compensation, maintains high power and lowers fuel consumption.
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.
- The cutting arm is reversible which lets you cut closer to walls or the ground. The drive belt has a fully sealed transmission. This keeps out cutting dust etc, reducing wear.
- Reduces wear and slippage risk.
- Compact design, low weight and correctly positioned handles make our machines easier to handle. Also, our anti-vibration system in the handles provides a more convenient handling during long shifts.
- DEX (Dust Extinguisher System)
- X-torq®
- Elevated startability - the new digital ignition system makes the cutter easier to start in any situation. Because of the strong spark the machine starts quickly, which allows you to maximise your work time.
- The new K 760 has a new, light blade guard made of durable magnesium that makes cutting easier. Thanks to stepless adjustment, you can quickly and easily change the cutting position.
- The new wet cutting system makes dust control easier. A progressive valve allows exact adjustment of the water volume, greatly reducing water consumption and slurry.
- New tank ventilation ensures good air supply to the fuel tank and prevents dust from entering the tank, which means more reliable operation and longer intervals between servicing.
- Easy interchangeable blade bushing.

TECHNICAL SPECIFICATION

Engine	Air-cooled 2 stroke engine
Cylinder displacement	4.48 cu.inch
Power output	5 hp
Fuel tank volume	30.4 fl oz
Idling speed	2700 rpm
Vibrations front handle	2.4/2.4 m/s ²
Vibrations front handle	0/0/0 m/s ²
Vibrations rear handle	2.4/2.4 m/s ²
Sound pressure level at operators ear	101 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Blade diameter	12/14"
Max cutting depth	4/5"
Weight (excl. cutting equipment)	21.2/21.6 lbs
Fuel tank volume	1.9 US pint

